

WOOD guard TC™

TOP COAT



Photo courtesy of Southland Log Homes



EXTERIOR & INTERIOR COATING

ACRYLIC TRANSPARENT LATEX COATING

WORKS ON TOP OF WOODGUARD FOR EXTERIOR AND WOODGUARD ITF FOR INTERIOR

KEEP OUT OF REACH OF CHILDREN

CAUTION! IRRITANT

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

Distributed by:

ISK Biocides, Inc.

416 East Brooks Road • Memphis, TN 38109

- **Ideal for Log Homes**
- **Seals Out Dust, Dirt, Household Odors and Moisture**
- **Water-Repellent, Breathable Finish**
- **Low-Odor, Fast-Drying, Ammonia-Free**
- **Easy to Apply: Brush, Roll or Spray**
- **Soap and Water Clean-up**
- **VOC-Compliant**
- **Water-Based Technology**

PRECAUTIONS:

Do not take internally. Avoid prolonged contact with skin. May cause irritation, especially with prolonged or repeated exposure. Wash thoroughly after handling. Avoid direct contact with eyes. May cause redness and pain. Wear eye protection when using this product. Use in a well-ventilated area. If adequate ventilation is not available, wear a vapor/mist respirator.

FIRST AID:

IF INHALED: Remove to fresh air. Get medical attention for any breathing difficulty.

IF INGESTED: Treat symptomatically and supportively. Seek medical attention.

IF ON SKIN: Wash exposed area with soap and water. Get medical advice if irritation develops.

IF IN EYES: Wash thoroughly with running water. Get medical advice if irritation develops.

STORAGE:

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. **DO NOT ALLOW TO FREEZE.**

CONTAINER DISPOSAL: Dispose of empty containers in accordance with current applicable state and local regulations.

DIRECTIONS FOR USE

WOODguard TC™ is a clear acrylic latex top coat for use over interior or exterior pigmented stains such as WOODguard ITF™ (Interior Transparent Finish) and WOODguard® oil-based wood preservative.

APPLICATION:

Brush, roll or spray application is suitable, but the preferred application method is **airless sprayer**. When spraying, you will need to back brush or roll the sprayed surfaces immediately to maintain a sheer, even, translucent appearance. Because WOODguard TC dries very quickly, the spray application option may be a two-person job – one with a sprayer and one with a brush or low-nap roller. Regardless of application method, maintain a wet edge to prevent lap marks.

To apply over WOODguard oil-based wood preservative, you must allow two to three weeks or longer to pass, depending on temperature and humidity, to allow the WOODguard to cure before application. Do not apply if the overnight low temperature is below 50°F/10°C or the daytime high temperature is above 95°F/35°C. Do not apply during rain or excessive humidity. For two coat application, allow six to eight hours for WOODguard TC to dry between coats in warm and dry conditions. Cure time is dependent on temperature and humidity. When applying over WOODguard ITF, allow 2 - 3 days before applying WOODguard TC.

COVERAGE:

WOODguard TC will cover approximately 300 to 450 square feet per gallon on smooth, dry wood when proper application techniques are employed. On rough wood, coverage may be considerably less. On second coat, coverage will generally be more.

TINTING:

WOODguard TC is tintable with universal pigments. Consult your dealer for assistance in pigmentation to a semi-transparent stain. WOODguard TC tints fast and requires very little pigment. Pre-testing tints is recommended.

CLEAN-UP:

Cleans up with soap and water.

WARRANTY AND LIMITATION OF DAMAGES

Seller warrants to those persons lawfully acquiring title to this product that at the time of the first sale of this product by seller this product conformed to its chemical description and that it was reasonably fit for the purposes stated on the product label when used both in accordance with the Directions for Use appearing on the product label and under normal conditions of use. Buyers and users of this product assume the risk of all loss or damage from use or handling of this product that results from their failure to read and comply with the Directions for Use of this product which appear on the product label. **SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO.** Unless expressly prohibited by state law, the liability of seller for any breach of warranty shall not exceed the purchase price of the product as to which a claim is made.

®WOODguard is a registered trademark of IBC Manufacturing Company.

™WOODguard TC and WOODguard ITF are trademarks of IBC Manufacturing Company.