



Protecting and enhancing wood finishes since 1910.



Marine Formula

SEALER ONLY

Product #: TB 3809

More Info: waterlox.com/marine

Please Note:

This product is a sealer only. You must finish your wood with the Waterlox Marine Finish (TB 3940 or TB 6032). Use this product prior to finishing to seal your wood.



Product Details:

- Our product number is TB 3809.
- Formulated as a traditional exterior penetrating Tung oil sealer/primer.
- Penetrates and waterproofs when used as the sealer/primer coat(s) in conjunction with Waterlox Original Marine Finish.
- Like all of our Tung oil finishes, 90% of the resin portion of the formula is from renewable, natural resources.

Product Uses:

- For exterior projects, when used as a sealer only, apply 2 coats to prime/seal, followed by 2 coats of Marine Finish.
- Excellent for use as a primer, tie-coat or paint additive to improve adhesion.
- Exceptional adhesion to oily, dense, exotic woods like teak, rosewood and ipe.
- Waterlox Original Sealer/Finish (TB 5284) can be used interchangeably with Waterlox Original Marine Sealer (TB 3809).
- Coverage. One gallon covers 500 square feet per coat. One quart covers 125 square feet per coat. The number of coats depends upon the porosity of the wood. No thinning necessary.
- Dry time. Minimum of 24 hours between coats. Poor ventilation, high humidity or cool temperatures may increase dry times.