

WOODguard® SWO

(Swedish Wood Oil™)
Especially For Pressure-Treated Wood

Product Data Sheet

PRODUCT DESCRIPTION AND BASIC USE:

WOODguard® SWO is a clear, water repellent that helps retard warping, cupping, splitting and nail popping. Especially designed for pressure-treated lumber. Restores lubricity lost in wood during pressure treatment. Will never crack or peel.

WOODguard SWO is a colorless, water-repellent treatment for pressure treated wood. Pressure treatment effectively preserves wood against insect attack and degradation from mold and fungal growths. It is not, however, immune from the damaging effects of water. Pressure treatment causes wood to become highly porous and water absorbent. In winter, water will freeze in the pores of the wood cell structure and then thaw, eventually causing the wood to become brittle. Direct sun and heat of summer further dry the wood, which eventually warps and splits long before it ever rots from decay.

FEATURES:

WOODguard SWO is absorbed into the wood and bonds with the cell structure. The oils lubricate and stabilize the wood while repelling water. It helps retard warping, cupping, splitting and nail popping. One moderate coat promotes dimensional stability, and special penetrating oils restore the natural lubricity of the wood often lost in the pressure-treating process. **Woodguard SWO** is recommended for use on pressure treated wood decks, fences, storage buildings and all other pressure-treated wood construction projects.

APPLICATION:

WOODguard SWO is easy to use. It can be brushed, rolled or sprayed. Apply above 50 degrees F for fastest cure time (Below 50 degrees F, **WOODguard SWO** may become too viscous to spray). One moderate coat is sufficient. Do not over apply. Use only as much as can be readily absorbed by the wood. Surfaces should be cleaned and free of all loose debris. When using wood that has not been kiln dried, wait six months after construction before treating for maximum penetration. Moisture content of wood should be less than 18%.

COLOR:

WOODguard SWO dries into the wood and does not provide any color. Application of **WOODguard SWO** will give wood an oiled appearance which weathers out to a silvery grey color over time. Most alkyd/oil-based stains can be applied over **WOODguard SWO** after two weeks cure period. It is best to apply this dual treatment first to a small remote surface in order to verify compatibility. Do not attempt to apply latex finishes/stains over **WOODguard SWO**.

SUBSEQUENT TREATMENTS:

WOODguard SWO can be re-applied when the surface exhibits signs of water absorption.

PRECAUTIONARY STATEMENTS:

CAUTION. Keep out of reach of children. This product contains petroleum distillates. Avoid contact with eyes. Harmful if swallowed. Avoid breathing spray mist.

ENVIRONMENTAL HAZARDS:

Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not use near heat or open flame.

FIRST AID:

If In Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.

If Swallowed: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.

Hot Line Number: In case of emergency, call Chemtrec toll free at 1-800-424-9300. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

STORAGE AND DISPOSAL:

Storage: Store in a secure, well-ventilated area protected from extreme temperatures. Do not transfer to unmarked containers. Keep container closed when not in use.

Disposal: If Empty: Do not reuse this container. Place in trash or offer for recycling if available.

If Partially Filled: Call your local solid waste agency or 1-800-CLEANUP for disposal instructions. Never place unused product down any indoor or outdoor drain.

COVERAGE:

WOODguard SWO coverage: 75-300 sq. ft/gal

AVAILABILITY:

WOODguard SWO is available in 1 gal. can (4x1 gallon case), 5 gal. pail

Visit our website www.WOODguard.com or call 800-238-2523 for the dealer nearest you.

WARRANTY AND LIMITATION OF DAMAGES:

Seller warrants to those persons lawfully acquiring title to this product that at the time of the first sale of this product by seller this product conformed to its chemical description and that it was reasonably fit for the purposes stated on the product label when used both in accordance with the Directions for Use appearing on the product label and under normal conditions of use. Buyers and users of this product assume the risk of all loss or damage from use or handling of this product that results from their failure to read and comply with the Directions for Use of this product, which appear on the product label. **SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO.** Unless expressly prohibited by state law, the liability of seller for any breach of warranty shall not exceed the purchase price of the product as to which a claim is made.

ISK Biocides, Inc.

416 E. Brooks Rd. - Memphis, TN 38109

Ph: 800-238-2523

Fax 901-344-5388

WOODguard® is a registered trademark of IBC Manufacturing Company.

Swedish Wood Oil™ is a trademark of ISK Americas Incorporated.